



Domekt CF 200 F C8

Maximal air flow, m³/h	202
Maximal air flow, l/s	56
Reference flow rate, m³/s	0,039
Reference pressure difference, Pa	50
SPI, W/(m³/h)	0,19
Thermal efficiency of heat recovery, %	90
Electric air heater capacity, kW / Δt, °C	0,5/10,3
Supply voltage, V	1~230
Maximal operating current HE, A	3,2
Power supply cable, mm²	3×1,5
Electric power input of the fan drive at maximum flow rate, W	41
Electric power input of the fan drive at reference flow rate, W	14
Noise power level, L _{WA} dB(A)	42
Noise pressure level, L _{PA} dB(A), (3 m)	31
Filters dimensions B×H×L, mm	250×232×46
Supply filter class	ePM1 60 (F7)
Exhaust filter class	ePM10 50 (M5)
Unit dimensions B×H×L, mm	560×294×1100
Maintenance space, mm	300
Unit weight, kg	28



Performance

Unit with standard equipment



Accessories

Closing damper	AGUJ-M-160+TF230/CM230
Silencer	ODA/EHA ASTS-160-600-M
	SUP/ETA ASTS-160-900-M
Water heater	DH-160
PPU	PPU-HW-3R-15-0,4-W2
2-way valve (heater)	VVP47.10-0,25+SSF161.05HF
Outdoor grill	LD-160

Mounting positions




Temperature efficiency

	Winter					Summer		
Outdoor temperature, °C	-23	-15	-10	-5	0	25	30	35
After heat exchanger, °C	17,5	18,3	18,8	19,3	19,8	22,3	22,8	23,4

indoor +22 °C, 20 % RH

Shown as left (L1)

View from inspection side



ODA – outdoor intake SUP – supply air ETA – extract indoor EHA – exhaust air