


EM 400 E4M 01


129165

- Innovative, high-efficiency diagonal fan
- Optimally tuned, CFD-optimized aerodynamics
- Housing made of impact-resistant, reinforced polypropylene
- Robust AC motor, 3-steps controllable
- Conveyed medium temperature up to 60 °C in continuous operation
- The benchmark for efficiency since 2012



FAN CURVES

Name	Value	Unit
Volume flow	0	m³/h
Pressure	0	Pa



to the product detail page

EM 400 E4M 01

129165

ruck

GENERAL DATA

Name	Value	Unit	Formula symbol
Labeling	CE, UKCA		
Duct size	-		WxHduct
Pipe connection size (DN)	DN400		DN
Rated voltage (entire device)	230	V	U _{rated}
Phases (entire device)	1~		phase
Electrical protection (entire device)	6 A		fuse
Housing material	Plastic		mat _{casing}
Impeller material	Plastic		mat _{impeller}
IP-protection class (entire device)	IPX4		IP _{compl}
IP-Protection class (terminal box)	IP44		IP _{ebox}
Weight	15.7	kg	m
Fan type	Diagonal		Fan _{type}
Category / Installation situation	A		cat

MAXIMAL DATA

Name	Value	Unit	Formula symbol
Max. power consumption (device)	211	W	P _{ed, max}
Max. operating current (device)	1	A	I _{ed, max}
Max. speed	1440	1/min	n _{max}
Max. stat. efficiency	47.2	%	η _{es}
Max. fan efficiency	51	%	η _e
Max. flowrate	3300	m ³ /h	Q _{v, max}
Max. stat pressure	270	Pa	p _{sf, max}
Max. medium temperature	60	°C	T _{m, max}
Max. environment temperature	60	°C	T _{amb, max}
Min. environment temperature	-25	°C	T _{amb, min}
Min. voltage	230	V	U _{min}



MOTOR DATA

Name	Value		Unit	Formula symbol
	50 Hz	60 Hz		
Rated frequency (device)		50		f
Motor type		AC 1~		phase
Installation type		IRM (In)		install
Rotation direction		right		rotation
Isolation class		ISO F		ISOclass
Motor-protection		TAI		protectmotor
Protection class		IP00		IPmotor
Is pole-changeable		No		polexch
Type of power supply		AC 1~		pwrsupmotor
Capacity capacitor		7	μF	Ccond
Voltage capacitor		450	V	VUcond
Number of poles (1)		4.000000		num polesw1
Rated voltage	230		V	U _{rated, f1}
Rated current	1.05		A	I _{rated, f1}
Shaft power	120		W	P _{out, f1}
UL-Certification motor		None		ULcert

ERP DATA (LOT11)

Name	Value	Unit	Formula symbol
Speed at the energy efficiency optimum	1414	1/min	n _{opt}
Efficiency level	47.5	%	N
Efficiency category	statisch		catefficiency
Input power of the motor at the energy efficiency optimum	0.21	kW	P _{e, opt}
Overall efficiency	65.2	%	η _{ges}
Measurement category	A		meas cat
Fan pressure at energy efficiency optimum	178	Pa	p _{f, opt}
Flowrate at energy efficiency optimum	2118	m ³ /h	Q _{v, opt}



to the product detail page